

12674-58-6

Closet Carrier

Left Hand

Specification

Josam 12674-58-6 series coated cast iron long barrel left-hand horizontal 4" no-hub fitting with 2" no-hub vent and adjustable carrier body, ABS extension with integral test cap, pylon feet, anchor foot, plated hardware and neoprene fixture gasket, invertible faceplate for siphon jet or blowout closets with supply pipe support.

△ For dimension shorter than 5-1/2" (1" min) cut extension.
For longer extension (10-1/2" max) specify (-10).


☒ Recommend feet be secured to floor with 1/2" bolts and anchors (by others).

⊗ For siphon jet roughing over 6" or blowout roughing over 12-1/2" specify on order.

Siphon jet dims shown.
For blowout dims, use:

□ Min 2" and max 4".

▤ Min 11" and max 16-1/2".



	-PF	Pylon foot, STD.
	-OR	O-ring carrier
	-SDH	Special duty 750 LB carrier
	-HS	Hub and spigot
	-AUX	Auxiliary inlet
	-VP	Vandal-proof trim
	-1	Positioning frame
X	-6	Supply pipe support (specify type of pipe)

	-10	ABS extension through 10-1/2" wall
	-24	Floor mounted back outlet china bowl
	-30	Cast iron adj. extension w/ connector
	-30-2	Cast iron adj. ext. w/connector and test cap
	-32	Carrier for wide chase installations
	-35	Carrier for wheelchair high rough
X	-58	Long barrel fitting
	-XSD	Extra special duty 1,000 LB capacity

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



A WATTS Brand