

12694-HS

Closet Carrier Back-To-Back Specification

Josam 12694-HS series coated cast iron double horizontal 4" hub & spigot fitting with 2" hub & spigot vent and adjustable carrier body, ABS extension with integral test cap, pylon feet, plated hardware and neoprene fixture gasket, invertible for siphon jet or blowout closets. 500 LBS capacity.

△ For dimension shorter than 5-1/2" (1" min) cut extension. For longer extension (10-1/2" max) specify (-10).



Siphon jet dims shown.
For blowout dims, use:

□ Min 2" and max 4"

☒ Recommend feet be secured to floor with 1/2" bolts and anchors (by others).

△ Min 11" and max 16 1/2"

⊗ For siphon jet roughing over 6" or blowout roughing over 12-1/2" specify on order.



	-PF	Pylon foot, std.
	-OR	O-ring carrier
X	-HS	Hub & spigot
	-AUX	Auxiliary inlet, 2"
	-VP	Vandal-proof trim
	-1	Positioning frame
	-6	Supply pipe support (specify type of pipe)

	-10	ABS extension through 10-1/2" wall
	-24	Floor mounted back outlet china bowl
	-30	Cast iron adj. extension w/ connector
	-30-2	Cast iron adj. extension w/ connector and test cap
	-32	Carrier for wide chase installations
	-35	Carrier for wheelchair high rough
	-58	Horizontal hub and spigot long barrel

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



A WATTS Brand