14464


Closet Carrier Single Close With 4" Vent

Specification

Josam 14464 series coated cast iron single vertical 4" no-hub single fitting with 4" no-hub vent, adjustable carrier body, invertible for siphon jet or blowout closets, with ABS extension with integral test cap, pylon feet, plated hardware and neoprene fixture gasket.

- For dimension shorter than 5-1/2"
 (1" min) cut extension for longer extension (10-1/2" max) specify (-10).
- ☑ Recommend feet be secured to floor with 1/2" bolts and anchors (by others).
- Solution For siphon jet roughing over 6" or blowout roughing over 12-1/2" specify on order.
 - Siphon jet dims shown. For blowout dims, use:

∠ Min 11" and max 16 1/2".



4" NO-HUB VENT ANCHOR FOOT 4 3/8 [21] 3 4 3/8 [110] 9 1/4 [234] 5 1/2 MAX FIXTURE GASKET WALL FINISHED WALL	7 1/2 13 3/4 [349] 4 MIN 9 MAX POOT M FOOT M ADJUSTABLE FOR AUX	3 7/8 [97] 2 [51] 3 7/8 [97] 2 [51]
WALL J GAGNET	FOOT ⊠ 71/2 AUX LEF RIGI	T SIDE (-45) HT SIDE (-46) 5 MAX [127]

-SD	Special duty 500 LB carrier
-VP	Vandal-proof trim
-1	Positioning frame
-6	Supply pipe support (specify type of pipe)
-10	ABS extension through 10-1/2" wall
-24	Carrier for floor mounted back outlet china bowls

-30	Cast iron adj. ext. w/ connector	
-30-2	Cast iron adj. ext. w/ connector and test cap	
-45	Threaded left-hand auxiliary inlet	
-46	Threaded right-hand auxiliary inlet	
-SDH	Special duty high 750 LB carrier	
-XSD	Extra special duty 1,000 LB carrier	

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



ES-J-14464 2505 © 2025 Josam