21500-AE-ORDG1

Roof Drain

Green Roof

Specification

Josam series 21500-AE-ORDG1 coated cast iron drain body with adjustable extension and clamp ring with stainless steel gravel stop and secured cover and PVC standpipe with orifice

Ø15 1/4 SS COVER [387] Ø13 1/8 [333] 3/8" PERFORATED SS GRAVEL STOP (40% OPEN) Ø6 5/8 PVC STANDPIPE WITH ϕ 5/8" ORIFICE [168] (12" STD.) (10-1/2" STD.) Ø WEJLOC CLAMP RING AND GRAVEL STOP MIN. 1-1/2 MAX. 4 TION C564 PIPE DECK CLAMP (-1) SIZE X = 5-3/8Ø13 1/4 Y = 4-7/8[330] Z = 5-1/8MIN. DECK OPENING

•	THIS DIMENSION IS 5-3/4" FOR 21508-T
•	GASKET ON -Y CONNECTI CONFORMS WITH ASTM-C

	2"	Pipe Size
	3"	Pipe Size
	4"	Pipe Size
	5"	Pipe Size
	6"	Pipe Size
	8"	Pipe Size
	10"	Pipe Size (No-Hub Only)
	-X	Inside Caulk Outlet
	-Y	Hub outlet w/gasket (2", 3" & 4" sizes only)
	-Z	No-Hub Spigot Outlet
	-T	Threaded Outlet
Х	-AE	Threaded Leveleze Adj. Ext.
	-AER	Adj. Ext. Using Threaded Rods

T = 3-3/4

-PC	Perforated Cover
-LO	Less Orifice In Standpipe
-1	Deck Clamp Asy.
-2	Drain Receiver
-3	Deck Clamp Asy. And Drain Receiver
-3C	Drain Receiver And Drain Receiver Clips
-4	Secondary Flashing Clamp (-AE Only)
-6	Extra Wide Flange Drain Body (-X Outlet Only)
-10	Fixed Ext. Collar, Cast Iron (Specify Ht. Or 4" Std.)
-10-20	Fixed Ext. Collar, Galv. (Specify Ht. Or 4" Std.)
-17*	2" High Solid Clamping Collar
-20	Galv. Cast Iron Parts
-66	No-Hub Side Outlet (2" Thru 6" Outlets Only)

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:

T: (800) 365-6726 • Josam.com A WATTS Brand

ES-J-21500-AE-ORDG1 2411 © 2024 Josam