21500-ORDG1-6

Roof Drain Green Roof

Specification

Josam series 21500-ORDG1-6 coated cast iron large sump wide Ø20 flange drain body and clamp ring [508] with stainless steel gravel stop and secured cover and pvc standpipe Ø13 1/8 with orifice. [333] Ø6 5/8 SS SOLID COVER [168] WITH SCREWS Ø3/8" PERFORATED ೲೲೲ SS GRAVEL STOP (40% OPEN) PVC STANDPIPE WITH Ø5/8" ORIFICE (12" STD.) (10-1/2" STD.) WEJLOC CLAMP RING WITH GRAVEL STOP 7 3/4 [197]

> → PIPE → SIZE →

Ø 13-1/4

	2"	Pipe Size
	3"	Pipe Size
	4"	Pipe Size
	5"	Pipe Size
	6"	Pipe Size
Х	-X	Inside Caulk Outlet
	-AE	Adjustable Extension
	-PC	Perforated Cover

	-LO	Less Orifice In Standpipe
	-1	Deck Clamp Assy.
Х	-6	Extra Wide Flange Drain Body (-X Outlet Only)
	-10	Fixed Ext. Collar, Cast Iron (Specify Ht. Or 4" Std.)
	-10-20	Fixed Ext. Collar, Galv. (Specify Ht. Or 4" Std.)
	-17*	2" High Solid Clamping Collar
	-20	Galv. Cast Iron Parts
	-66	No-Hub Side Outlet (2" Thru 6" Outlets Only)

MIN 1 MAX 4-3/4

DECK CLAMP

(-1 OPTION)

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:

JOSAM°

T: (800) 365-6726 • Josam.com

A WATTS Brand

ES-J-21500-ORDG1-6 2411 © 2024 Josam